jaga

CLIMATE DESIGNERS

Heating

PANEL PLUS HORIZONTAL kr. 2024.DK



kr. DK 01/2024

jaga
CLIMATE DESIGNERS

PANEL PLUS HORIZONTAL

Elegant simplicity and power

Streamlined, elegant design. The compact style of the Panel Plus allows creative freedom to the designer and saves space too! The Panel Plus can be fitted as a wall mounted radiator, but Jaga also offers a super compact, solid skirting model starting at a height of 6 cm! The robust design of the Panel Plus radiator with its hidden collectors provides an elegant simplicity that oozes quality.

Vertical version: see p. 112.
Freestanding version: see p. 156.

PANEL PLUS HORIZONTAL sandblast grey 001



PANEL PLUS HORIZONTAL

PANEL PLUS HORIZONTAL

DIMENSIONS *(in cm)*

standard connection

variant





Vertical version: see p. 112.
Freestanding version: see p. 156.

DELIVERY

- connection 18 underneath
- wall fixing
- chrome-plated air vent and drain plug G1/2”
- pre-mounted grille
- type 11 is provided with standard and extended wall fixings

COLOURS

Environmentally friendly, scratch-resistant, high UV resistant powder coating.

Standard colours:
- traffic white RAL 9016 (333), smooth satin matt
- sandblast grey (001), fine texture metallic
- off-black RAL 7021 (145) Soft touch: finely-textured matte look, gloss degree ‹ 10%

Other colours: see colour chart.

CONNECTION

Code:
1° number = flow
2° number = return

Standard connection:
Code 18, reversible 18 or 81



Other connections (no surcharge):
- side connection:
  one-sided: code 32 or 67 instead of 18
  cross-over: code 37 or 62 instead of 18
- single point connection: code 11 (left) or 88 (right) instead of 18.
  Always use a vertical diffusion tube (ø 10 to 12mm) min. 100 mm long and a reduction washer.

CONNECTION SETS

Example showing connection set to the wall
Jaga Deco double angled

TRV head and sleeve couplings included.

set 35 To the wall	Kr.
CODE.JH2.AC.1...	1643

fill in sleeve coupling code

Precision metal tube 15/1	**115**
Precision metal tube 16/1	**116**
Precision metal tube 18/1	**118**
RPE/ALU tube 16/2	**316**
RPE/ALU tube 18/2	**318**

Other connection sets and sleeve couplings

see chapter “Connection sets and valves” for all connection options and technical information

PANEL PLUS HORIZONTAL

code	height	length	type	colour	conn.
PPHW .	018	100	11 .	XXX	/18 /GR

fill in colour code

L H 018

	Type	Watts 75/65	Watts 55/45	Kr. st. colour	Kr. other
060	---	---	---	---	---
	---	---	---	---	---
080	---	---	---	---	---
	---	---	---	---	---
100	11	389	204	3240	3885
	22	626	312	6045	7260
120	11	466	244	3570	4283
	22	751	374	6623	7973
140	11	544	285	3923	4695
	22	876	436	7238	8678
160	11	622	326	4268	5130
	22	1001	498	7853	9420
180	11	699	367	4613	5543
	22	1126	561	8430	10118
200	11	777	408	4943	5933
	22	1252	623	9008	10808
220	11	855	449	5295	6353
	22	1377	686	9608	11535
240	11	932	489	5625	6750
	22	1502	748	10170	12225
260	11	1010	530	5978	7170
	22	1627	810	10800	12960
280	11	1088	571	6300	7568
	22	1752	872	11378	13658
300	11	1166	612	6660	8003
	22	1877	935	11970	14355

L H 024

	Type	Watts 75/65	Watts 55/45	Kr. st. colour	Kr. other
060	11	285	150	2850	3405
	22	477	238	5475	6578
080	11	380	199	3248	3893
	22	636	317	6188	7418
100	11	475	249	3638	4365
	22	794	395	6885	8273
120	11	570	299	3990	4808
	22	953	475	7523	9030
140	11	665	349	4365	5243
	22	1112	554	8160	9788
160	11	760	399	4755	5723
	22	1271	633	8843	10628
180	11	855	449	5130	6150
	22	1430	712	9480	11385
200	11	950	498	5483	6593
	22	1589	791	10118	12143
220	11	1045	548	5858	7043
	22	1748	870	10755	12923
240	11	1140	598	6240	7478
	22	1907	950	11423	13703
260	11	1235	648	6600	7913
	22	2065	1028	12075	14498
280	11	1330	698	6975	8363
	22	2224	1107	12713	15270
300	11	1425	748	7343	8790
	22	2383	1187	13350	16020

L H 031

	Type	Watts 75/65	Watts 55/45	Kr. st. colour	Kr. other
060	11	334	175	3315	3968
	22	571	284	6420	7710
080	11	445	233	3780	4553
	22	761	379	7290	8753
100	11	556	292	4245	5100
	22	951	474	8138	9765
120	11	668	350	4680	5618
	22	1142	569	8895	10673
140	11	779	409	5168	6203
	22	1332	663	9788	11753
160	11	890	467	5618	6750
	22	1522	758	10583	12705
180	11	1001	525	6068	7275
	22	1713	853	11415	13695
200	11	1113	584	6518	7823
	22	1903	948	12240	14670
220	11	1224	642	6960	8363
	22	2093	1042	13035	15638
240	11	1335	700	7433	8925
	22	2283	1137	13868	16628
260	11	1446	759	7890	9465
	22	2474	1232	14708	17640
280	11	1558	817	8370	10043
	22	2664	1327	15585	18698
300	11	1669	876	8843	10628
	22	2854	1421	16418	19710

L H 037

	Type	Watts 75/65	Watts 55/45	Kr. st. colour	Kr. other
060	11	380	199	3788	4560
	22	659	328	7425	8910
080	11	507	266	4335	5205
	22	879	438	8408	10095
100	11	633	332	4883	5850
	22	1098	547	9413	11295
120	11	760	399	5408	6510
	22	1318	656	10395	12465
140	11	887	465	5948	7133
	22	1538	766	11378	13665
160	11	1013	531	6480	7800
	22	1757	875	12390	14880
180	11	1140	598	7028	8423
	22	1977	984	13358	16028
200	11	1267	665	7553	9075
	22	2197	1094	14348	17235
220	11	1394	731	8085	9720
	22	2416	1203	15330	18398
240	11	1520	797	8648	10358
	22	2636	1313	16328	19590
260	11	1647	864	9150	11010
	22	2856	1422	17303	20768
280	11	1774	931	9698	11633
	22	3075	1531	18278	21938
300	11	1900	997	10230	12270
	22	3295	1641	19245	23100

L H 043

	Type	Watts 75/65	Watts 55/45	Kr. st. colour	Kr. other
060	11	425	223	4268	5123
	22	742	369	8370	10043
080	11	566	297	4890	5858
	22	989	492	9533	11423
100	11	708	371	5483	6593
	22	1236	615	10673	12810
120	11	849	445	6113	7343
	22	1483	738	11835	14220
140	11	991	520	6728	8078
	22	1730	861	12998	15600
160	11	1132	594	7358	8828
	22	1978	985	14145	16973
180	11	1274	668	7995	9593
	22	2225	1108	15323	18390
200	11	1415	742	8603	10335
	22	2472	1231	16463	19763
220	11	1557	817	9218	11048
	22	2719	1354	17618	21128
240	11	1698	891	9818	11798
	22	2966	1477	18773	22553
260	11	1840	965	10448	12563
	22	3214	1600	19943	23925
280	11	1981	1039	11078	13313
	22	3461	1723	21113	25335
300	11	2123	1114	11708	14055
	22	3708	1846	22298	26753

L H 050

	Type	Watts 75/65	Watts 55/45	Kr. st. colour	Kr. other
060	11	468	246	4748	5693
	22	819	408	9353	11228
080	11	624	327	5453	6540
	22	1092	544	10665	12795
100	11	780	409	6128	7350
	22	1365	680	11963	14340
120	11	936	491	6818	8205
	22	1638	816	13283	15945
140	11	1091	572	7523	9038
	22	1911	952	14603	17520
160	11	1247	654	8228	9900
	22	2185	1088	15930	19118
180	11	1403	736	8933	10718
	22	2458	1224	17250	20700
200	11	1559	818	9630	11573
	22	2731	1360	18585	22313
220	11	1715	900	10335	12390
	22	3004	1496	19890	23865
240	11	1871	982	11040	13253
	22	3277	1632	21240	25485
260	11	2027	1063	11753	14108
	22	3550	1768	22590	27090
280	11	2183	1145	12443	14948
	22	3823	1904	23895	28658
300	11	2339	1227	13148	15773
	22	4096	2040	25178	30240

EN442 output at 20°C room temperature

PANEL PLUS HORIZONTAL

L	Type	Watts 75/65	Watts 55/45	Kr. st. colour	Kr. other
	H 056				
060	**11**	510	268	**5213**	**6255**
	22	892	444	**10335**	**12390**
080	**11**	680	357	**5993**	**7193**
	22	1190	593	**11783**	**14138**
100	**11**	850	446	**6750**	**8078**
	22	1487	740	**13215**	**15848**
120	**11**	1020	535	**7530**	**9045**
	22	1784	888	**14730**	**17678**
140	**11**	1190	624	**8318**	**9975**
	22	2082	1037	**16208**	**19440**
160	**11**	1360	714	**9105**	**10920**
	22	2379	1185	**17700**	**21240**
180	**11**	1530	803	**9878**	**11865**
	22	2676	1333	**19185**	**23025**
200	**11**	1700	892	**10673**	**12810**
	22	2974	1481	**20708**	**24840**
220	**11**	1870	981	**11453**	**13740**
	22	3271	1629	**22185**	**26633**
240	**11**	2040	1070	**12248**	**14685**
	22	3569	1777	**23670**	**28418**
260	**11**	2210	1159	**13020**	**15623**
	22	3866	1925	**25163**	**30203**
280	**11**	2380	1249	**13785**	**16560**
	22	4163	2073	**26633**	**31958**
300	**11**	2549	1337	**14580**	**17475**
	22	4461	2221	**28110**	**33735**

L	Type	Watts 75/65	Watts 55/45	Kr. st. colour	Kr. other
	H 069				
060	**11**	592	310	**6083**	**7298**
	22	1025	510	**12083**	**14498**
080	**11**	789	414	**6938**	**8333**
	22	1367	681	**13733**	**16485**
100	**11**	986	517	**7823**	**9398**
	22	1709	851	**15420**	**18495**
120	**11**	1183	620	**8723**	**10470**
	22	2051	1021	**17160**	**20603**
140	**11**	1381	724	**9638**	**11580**
	22	2392	1191	**18915**	**22695**
160	**11**	1578	827	**10568**	**12683**
	22	2734	1361	**20708**	**24855**
180	**11**	1775	931	**11468**	**13778**
	22	3076	1532	**22448**	**26948**
200	**11**	1972	1034	**12413**	**14895**
	22	3418	1702	**24233**	**29078**
220	**11**	2169	1137	**13328**	**15998**
	22	3760	1872	**26003**	**31193**
240	**11**	2367	1241	**14250**	**17085**
	22	4101	2042	**27765**	**33323**
260	**11**	2564	1344	**15165**	**18210**
	22	4443	2212	**29550**	**35445**
280	**11**	2761	1448	**16073**	**19298**
	22	4785	2383	**31298**	**37545**
300	**11**	2958	1551	**16988**	**20408**
	22	5127	2553	**33068**	**39675**

L	Type	Watts 75/65	Watts 55/45	Kr. st. colour	Kr. other
	H 081				
060	**11**	671	352	**6810**	**8183**
	22	1143	569	**13583**	**16313**
080	**11**	895	469	**7748**	**9308**
	22	1524	759	**15383**	**18465**
100	**11**	1119	587	**8700**	**10433**
	22	1905	949	**17220**	**20655**
120	**11**	1342	704	**9720**	**11648**
	22	2286	1139	**19163**	**23003**
140	**11**	1566	821	**10718**	**12870**
	22	2667	1329	**21113**	**25335**
160	**11**	1790	939	**11730**	**14063**
	22	3048	1519	**23070**	**27668**
180	**11**	2013	1056	**12720**	**15278**
	22	3430	1709	**24998**	**30030**
200	**11**	2237	1173	**13740**	**16508**
	22	3811	1899	**26963**	**32378**
220	**11**	2461	1290	**14768**	**17723**
	22	4192	2089	**28950**	**34733**
240	**11**	2684	1407	**15765**	**18915**
	22	4573	2278	**30855**	**37043**
260	**11**	2908	1525	**16785**	**20138**
	22	4954	2468	**32828**	**39413**
280	**11**	3132	1642	**17783**	**21353**
	22	5335	2658	**34770**	**41730**
300	**11**	3356	1760	**18818**	**22568**
	22	5716	2848	**36743**	**44100**

EN442 output at 20°C room temperature

Panel Plus is available from 6cm high up to 94 cm, see: www.jaga.com

EN 442 EURONORM

jaga
QUALITY
MADE IN BELGIUM

MILTON
MEGATHERM

MILTON MEGATHERM A/S

Formervangen 14-16
DK - 2600 Glostrup

Tel: +45 4697 0000
Fax: +45 4697 0001

info@miltonmegatherm.dk
www.miltonmegatherm.dk

jaga

CLIMATE
DESIGNERS

Jaga International
Verbindingslaan 16
B-3590 Diepenbeek

Tel.: +32 (0)11 29 41 12
Fax: +32 (0)11 29 41 60
export@jaga.com

The information in this price list is correct at the time of printing.
Jaga reserves the right to change product specification at any time in line with our policy of continuous improvement and innovation.
All prices in DKK, exclude VAT. Prices valid from January 1, 2024.
Replaces all existing price lists.

281123 - JAGA N.V.