



CLIMATE DESIGNERS

Iguana Circo Wall

Material

Iguana Circo Wall is composed of vertical triangular steel radiation tubes (45 x 25 x 1.5 mm), welded on steel position brackets. The radiation tubes are hydraulically connected using steel bends. They are placed in a half circle next to each other with a 2.5 mm spacing.

Iguana Circo Wall is provided with a central connection MM G1/2" inner thread, axis distance 50 mm.

Standard for two pipe connection, one pipe is possible by using Jaga Deco Pro valves. 4 wall brackets and 2 air vent plugs G1/8" are included.

Iguana Circo Wall Plus is provided with 2 side panels which are attached to its extremities by means of magnets.

Pressure test: 9 bars Working pressure: 6 bars

Colour

- Iguana Circo Wall / Iguana Circo Wall Plus (with side panels) is lacquered in / the colour traffic white RAL 9016 (333), smooth satin finish / the colour sandblast grey (001) fine texture metallic / the colour ... (see colour chart).
- The radiators are sandblasted, degreased and phosphated. The coating is a scratch resistant epoxy-polyester powder, sprayed electrostatically and baked at a temperature of 200°C. UV-resistant due to ASTM G53. This high quality finish offers an optimal scratch resistance and is very easy to maintain. Thickness of the lacquer: min 80µ.

Manufacturer: Jaga

Model: Iguana Circo Wall / Iguana Circo Wall Plus Outputs meet standard EN 442.

Options

The towel rail and hat rack have the same radius as the radiator. They can also be ordered and fitted after installation.

- Towel rail and fixings in chrome-plated aluminium.
- Hat rack and fixings in chrome-plated aluminium, including 5 coat hooks.
- Guard with TRV and lockshield, for invisible connection to the wall or to the floor. Floorboards need to be removed for the guard.
- Jaga Deco connection sets and valves for two pipe
- Jaga Deco Pro connection sets and valves for two pipe or one pipe

How to install

The building services engineer chooses the radiators considering following conditions:

- a heat output calculation according to the standard...
- the heat output and the dimension tables of the Iguana Circo Wall / Iguana Circo Wall Plus radiators according to EN 442.
- the radiator may be wall mounted with the 4 wall brackets supplied.
- Iguana Circo Wall / Iguana Circo Wall Plus will be connected to a one pipe system / two pipe system
- the specially designed / thermostatic Jaga Deco valves / thermostatic Jaga Deco Pro valves / thermostatic Jaga Danfoss Pro valves / Jaga Deco manual valves / can be connected to / synthetic tube / RPE/ALU tube / precision metal tube / steeltube.
- Jaga Deco thermostatic heads chrome / Jaga Deco thermostatic heads chrome-white RAL 9016 / Jaga Deco thermostatic heads in brushed stainless steel effect / Jaga Deco thermostatic heads in anodized aluminum effect / Jaga Danfoss thermostatic heads chrome-plated / Jaga Danfoss thermostatic heads in anodized aluminum effect / not / to be fitted.